




## NUMINOS® MOVE XS

black recessed ceiling light, 2700K 20°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With various downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® MOVE XS recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS® from SLV?



## TECHNICAL DATA

|                                     |             |
|-------------------------------------|-------------|
| Item no.:                           | 1005553     |
| Secondary power / secondary voltage | 200mA       |
| Height                              | 5.5 cm      |
| Diameter                            | 8 cm        |
| Installation diameter               | 6.8 cm      |
| Installation depth                  | 11 cm       |
| Net weight                          | 0.11 kg     |
| Gross weight                        | 0.118 kg    |
| IP Code                             | IP 20       |
| Safety class                        | III         |
| Impact resistance class             | IK02        |
| Impact resistance                   | 0,2 Joule   |
| Assembly                            | Recessed    |
| Assembly details                    | Ceiling     |
| Wattage                             | 7 W         |
| Lumen                               | 640 lm      |
| Colour temperature                  | 2700 Kelvin |
| Beam angle                          | 20 °        |
| Color                               | black       |
| CRI                                 | 90          |
| UGR ≤                               | 16          |
| LXXBXX data                         | L80B50      |

## Light Source

|        |   |
|--------|---|
| 798300 |  |
|--------|---|

## Accessories

|         |   |
|---------|---|
| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector           |
| 1005610 | LED Driver , 200mA 10-W, Quick Connector                |
| 1005611 | LED Driver , 200mA 13,5W DALI dimmable, Quick Connector |
| 1005612 | NUMINOS® XS , diffuser                                  |
| 1005613 | NUMINOS® XS , transparent diffuser                      |
| 1005614 | NUMINOS® XS , frosted diffuser                          |
| 1005615 | NUMINOS® XS , black diffuser                            |

|                             |         |
|-----------------------------|---------|
| Service life                | 50000 h |
| Minimum ambient temperature | -20 °C  |
| Maximum ambient temperature | 40 °C   |
| BIG WHITE Page              | 39      |