




IN-LINE 22

48V spot, opal, DALI, black, 7.3W, 680lm, 4000K, CRI-90, 95°

Simple linear lights for a particularly elegant look. The IN-LINE linear luminaires form a unit in the 48V track system that only brings out the best: High-quality light in various lumen levels, lengths and colour temperatures, now also in 4,000 K. To integrate ambient lighting into modern interior design, there is a choice between fixed and swivelling versions as well as opal optics or darklight reflectors, which ensure perfect glare control and create a pleasant room atmosphere.



TECHNICAL DATA

Item no.	1006619
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly details	Track,Track Ceiling,Track Wall
Dimmable	Yes
Dimming technology	DALI 2
Primary nominal voltage	48V
Secondary power / voltage	350 mA
Safety class	III
Wattage	7.3 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Network rated standby power	0.5 W
Stroboscopic effect (SVM)	0.4
Lumen	680 lm
Colour temperature	4000 Kelvin
Beam angle	95 °
Color	matt black/black
CRI	90
UGR ≤	28

Light Source



LXXBXX data	L80B50
Service life	40000 h
Risk Group	1
Length	22 cm
Width	2.2 cm
Height	5.5 cm
Net weight	0.17 kg
Gross weight	0.22 kg