




IN-LINE 22

48V spot, opal, DALI, white, 7.3W, 680lm, 4000K, CRI-90, 95°

Simple linear lights for a particularly elegant look. The IN-LINE linear luminaires form a unit in the 48V track system that only brings out the best: High-quality light in various lumen levels, lengths and colour temperatures, now also in 4,000 K. To integrate ambient lighting into modern interior design, there is a choice between fixed and swivelling versions as well as opal optics or darklight reflectors, which ensure perfect glare control and create a pleasant room atmosphere.



TECHNICAL DATA

| | |
|-----------------------------------|--------------------------------|
| Item no. | 1006620 |
| Number of different light outlets | 1 |
| IP Code | IP20 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly details | Track,Track Ceiling,Track Wall |
| Dimmable | Yes |
| Dimming technology | DALI 2 |
| Primary nominal voltage | 48V |
| Secondary power / voltage | 350 mA |
| Safety class | III |
| Wattage | 7.3 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Network rated standby power | 0.5 W |
| Stroboscopic effect (SVM) | 0.4 |
| Lumen | 680 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 95 ° |
| Color | matt white/white |
| CRI | 90 |
| UGR ≤ | 28 |

Light Source



| | |
|---------------------|---------|
| LXXBXX data | L80B50 |
| Service life | 40000 h |
| Risk Group | 1 |
| Length | 22 cm |
| Width | 2.2 cm |
| Height | 5.5 cm |
| Net weight | 0.17 kg |
| Gross weight | 0.22 kg |