


IN-LINE 46

48V Spot, Move, Darklight Reflector, DALI, black, 14W, 1250lm, 4000K, CRI90, 35°

Simple linear lights for a particularly elegant look. The IN-LINE linear luminaires form a unit in the 48V track system that only brings out the best: High-quality light in various lumen levels, lengths and colour temperatures, now also in 4,000 K. To integrate ambient lighting into modern interior design, there is a choice between fixed and swivelling versions as well as opal optics or darklight reflectors, which ensure perfect glare control and create a pleasant room atmosphere.



TECHNICAL DATA

| | |
|-----------------------------------|--------------------------------|
| Item no. | 1006649 |
| Number of different light outlets | 1 |
| Rotating or tilting | tiltable |
| IP Code | IP20 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly details | Track,Track Ceiling,Track Wall |
| Dimmable | Yes |
| Dimming technology | DALI 2 |
| Primary nominal voltage | 48V |
| Secondary power / voltage | 350 mA |
| Safety class | III |
| Wattage | 14 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Rated standby power | 0.5 W |
| Stroboscopic effect (SVM) | 0.4 |
| Lumen | 1250 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 35 ° |
| Color | matt black/black |
| CRI | 90 |

Light Source



| | |
|------------------------------|---------|
| UGR \leq | 16 |
| LXXBXX data | L80B50 |
| Service life | 40000 h |
| Risk Group | 1 |
| Length | 45.5 cm |
| Width | 2.2 cm |
| Height | 5.8 cm |
| Net weight | 0.53 kg |
| Gross weight | 0.64 kg |