



TECHNICAL DATA

| | |
|-----------------------------------|--------------------------------|
| Item no. | 1006675 |
| Number of different light outlets | 1 |
| IP Code | IP 20 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly details | Track,Track Ceiling,Track Wall |
| Dimmable | Yes |
| Dimming technology | DALI |
| Primary nominal voltage | 48V |
| Secondary power / voltage | 200 mA |
| Safety class | III |
| Wattage | 8.7 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Network rated standby power | 0.5 W |
| Lumen | 690 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 55 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 25 |
| LXXBXX data | L80B50 |

Light Source

| | |
|--------|---|
| 798303 |  |
|--------|---|

Accessories

| | |
|---------|------------------------------------|
| 1005612 | NUMINOS® XS , diffuser |
| 1005613 | NUMINOS® XS , transparent diffuser |
| 1005614 | NUMINOS® XS , frosted diffuser |
| 1005615 | NUMINOS® XS , black diffuser |

| | |
|--------------|----------|
| Service life | 50000 h |
| Risk Group | 2 |
| Height | 8 cm |
| Diameter | 5 cm |
| Net weight | 0.178 kg |
| Gross weight | 0.19 kg |