



## TECHNICAL DATA

|                                   |                                |
|-----------------------------------|--------------------------------|
| Item no.                          | 1006712                        |
| Number of different light outlets | 1                              |
| IP Code                           | IP 20                          |
| Impact resistance class           | IK 02                          |
| Impact resistance                 | 0.2 Joule                      |
| Assembly details                  | Track,Track Ceiling,Track Wall |
| Dimmable                          | Yes                            |
| Dimming technology                | DALI                           |
| Primary nominal voltage           | 48V                            |
| Secondary power / voltage         | 350 mA                         |
| Safety class                      | III                            |
| Wattage                           | 16 W                           |
| Minimum ambient temperature       | -20 °C                         |
| Maximum ambient temperature       | 35 °C                          |
| Network rated standby power       | 0.5 W                          |
| Lumen                             | 1030 lm                        |
| Colour temperature                | 2700 Kelvin                    |
| Beam angle                        | 55 °                           |
| Color                             | black                          |
| CRI                               | 90                             |
| UGR ≤                             | 22                             |
| LXXBXX data                       | L80B50                         |

## Light Source

|        |   |
|--------|---|
| 791819 |  |
|--------|---|

## Accessories

|         |                                  |
|---------|----------------------------------|
| 1004786 | NUMINOS® S , diffuser<br>Ellipse |
| 1004787 | NUMINOS® S , diffuser<br>Prisma  |
| 1004788 | NUMINOS® S , diffuser<br>Frosted |
| 1004789 | NUMINOS® S , diffuser<br>Wabe    |

|              |          |
|--------------|----------|
| Service life | 50000 h  |
| Risk Group   | 1        |
| Height       | 9 cm     |
| Diameter     | 6 cm     |
| Net weight   | 0.326 kg |
| Gross weight | 0.349 kg |