



TECHNICAL DATA

| | |
|-----------------------------------|----------------------|
| Item no. | 1006844 |
| Number of different light outlets | 1 |
| IP Code | IP 20 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly details | Track, Track Ceiling |
| Dimmable | Yes |
| Dimming technology | DALI |
| Primary nominal voltage | 48V |
| Secondary power / voltage | 350 mA |
| Safety class | III |
| Wattage | 16 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Network rated standby power | 0.5 W |
| Lumen | 1120 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 40 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 19 |
| LXXBXX data | L80B50 |

Light Source

| | |
|--------|---|
| 791815 |  |
|--------|---|

Accessories

| | |
|---------|----------------------------------|
| 1004786 | NUMINOS® S , diffuser Ellipse |
| 1004787 | NUMINOS® S , diffuser Prisma |
| 1004788 | NUMINOS® S , diffuser Frosted |
| 1004789 | NUMINOS® S , diffuser Wabe |

| | |
|----------------|----------|
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 12.5 cm |
| Diameter | 6 cm |
| Pendant length | 150 cm |
| Net weight | 0.358 kg |
| Gross weight | 0.383 kg |