


NUMINOS® S

48V pendant light, pendant length 150cm, 4000K, 55°, DALI 2, matt black

High-quality minimalism across the board: the compact NUMINOS® pendant lights provide elegant yet effective illumination with a 48V track system. They also perfectly complement the most discerning room designs with their clear, cylindrical shape. The brightness, light colour (2700-K/3000K/4000K) and half-peak divergence (20°/ 40°/55°) of these DALI-compatible spotlights can be adjusted as desired. The aluminium housing is available in black, white and chrome. A CRI value over 90 ensures natural colour reproduction. The pendant lights are quick and easy to install thanks to the track adapter.



TECHNICAL DATA

Item no.	1006855
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly details	Track,Track Ceiling
Dimmable	Yes
Dimming technology	DALI 2
Primary nominal voltage	48V
Secondary power / voltage	350 mA
Safety class	III
Wattage	16 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Network rated standby power	0.5 W
Lumen	1130 lm
Colour temperature	4000 Kelvin
Beam angle	55 °
Color	matt black
CRI	90
UGR ≤	19
LXXBXX data	L80B50

Light Source

791831	
--------	---

Accessories

1004789	NUMINOS® S , diffuser Wabe
1004788	NUMINOS® S , diffuser Frosted
1004787	NUMINOS® S , diffuser Prisma
1004786	NUMINOS® S , diffuser Ellipse

Service life	50000 h
Risk Group	1
Height	12.5 cm
Diameter	6 cm
Pendant length	150 cm
Net weight	0.36 kg
Gross weight	0.47 kg