



## TECHNICAL DATA

|                                   |             |
|-----------------------------------|-------------|
| Item no.                          | 1006878     |
| Number of different light outlets | 1           |
| Assembly                          | Recessed    |
| Assembly details                  | Ceiling     |
| Secondary power / voltage         | 200 mA      |
| Safety class                      | III         |
| Minimum ambient temperature       | -20 °C      |
| Maximum ambient temperature       | 40 °C       |
| Lumen                             | 670 lm      |
| Colour temperature                | 2700 Kelvin |
| Beam angle                        | 20 °        |
| Color                             | white       |
| CRI                               | 90          |
| UGR ≤                             | 16          |
| LXXBXX data                       | L80B50      |
| Risk Group                        | 1           |
| Length                            | 8 cm        |
| Diameter                          | 4.9 cm      |
| Net weight                        | 0.24 kg     |
| Gross weight                      | 0.257 kg    |
| Shape of cut-out                  | round       |
| Installation depth                | 10 cm       |

## Light Source

|        |   |
|--------|---|
| 798300 |  |
|--------|---|

|                       |        |
|-----------------------|--------|
| Installation diameter | 6.8 cm |
|-----------------------|--------|

## Accessories

|         |   |
|---------|---|
| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector           |
| 1005610 | LED Driver , 200mA 10-W, Quick Connector                |
| 1005611 | LED Driver , 200mA 13,5W DALI dimmable, Quick Connector |
| 1005612 | NUMINOS® XS , diffuser                                  |
| 1005613 | NUMINOS® XS , transparent diffuser                      |
| 1005614 | NUMINOS® XS , frosted diffuser                          |
| 1005615 | NUMINOS® XS , black diffuser                            |