



TECHNICAL DATA

| | |
|-----------------------------------|-------------|
| Item no. | 1006985 |
| Number of different light outlets | 1 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 500 mA |
| Safety class | III |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Lumen | 1600 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 20 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 22 |
| LXXBXX data | L80B50 |
| Risk Group | 1 |
| Length | 13 cm |
| Diameter | 8 cm |
| Net weight | 0.75 kg |
| Gross weight | 0.803 kg |
| Shape of cut-out | round |
| Installation depth | 15 cm |

Light Source

| | |
|--------|---|
| 791800 |  |
|--------|---|

| | |
|-----------------------|---------|
| Installation diameter | 10.5 cm |
|-----------------------|---------|

Accessories

| | |
|---------|--|
| 1004054 | LED driver , 20W 500mA PHASE |
| 1004064 | LED driver , 21-29.5W 500/600/700mA |
| 1004069 | LED driver , 29W 500mA |
| 1004790 | NUMINOS® M , diffuser Ellipse |
| 1004791 | NUMINOS® M , diffuser Prisma |
| 1004792 | NUMINOS® M , diffuser Frosted |
| 1004793 | NUMINOS® M , diffuser Wabe |