



TECHNICAL DATA

| | |
|-----------------------------------|-------------|
| Item no. | 1007040 |
| Number of different light outlets | 1 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 700 mA |
| Safety class | III |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Lumen | 2150 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 20 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 22 |
| LXXBXX data | L80B50 |
| Risk Group | 1 |
| Length | 13 cm |
| Diameter | 10 cm |
| Net weight | 0.95 kg |
| Gross weight | 1.017 kg |
| Shape of cut-out | round |
| Installation length | 15 cm |

Light Source

| | | | |
|--------|---|-----------------------|-------|
| 791800 |  | Installation diameter | 13 cm |
|--------|---|-----------------------|-------|

Accessories

| | |
|---------|---|
| 1004062 | LED driver , 21-29.5W 500/600/700mA for Numi- nos Downlight Serie |
| 1004065 | LED driver , 30W 700mA |
| 1004070 | LED driver , 40W 700mA |
| 1004794 | NUMINOS® L , diffuser Ellipse |
| 1004795 | NUMINOS® L , diffuser Prisma |
| 1004796 | NUMINOS® L , diffuser Frosted |
| 1004797 | NUMINOS® L , diffuser Wabe |