



## TECHNICAL DATA

|                                   |             |
|-----------------------------------|-------------|
| Item no.                          | 1007045     |
| Number of different light outlets | 1           |
| Assembly                          | Recessed    |
| Assembly details                  | Ceiling     |
| Secondary power / voltage         | 700 mA      |
| Safety class                      | III         |
| Minimum ambient temperature       | -20 °C      |
| Maximum ambient temperature       | 40 °C       |
| Lumen                             | 2250 lm     |
| Colour temperature                | 2700 Kelvin |
| Beam angle                        | 55 °        |
| Color                             | white       |
| CRI                               | 90          |
| UGR ≤                             | 22          |
| LXXBXX data                       | L80B50      |
| Risk Group                        | 1           |
| Length                            | 13 cm       |
| Diameter                          | 10 cm       |
| Net weight                        | 0.95 kg     |
| Gross weight                      | 1.017 kg    |
| Shape of cut-out                  | round       |
| Installation length               | 15 cm       |

## Light Source

|        |   |
|--------|---|
| 791800 |  |
|--------|---|

|                       |       |
|-----------------------|-------|
| Installation diameter | 13 cm |
|-----------------------|-------|

## Accessories

|         |   |
|---------|---|
| 1004062 | LED driver , 21-29.5W<br>500/600/700mA for Numi-<br>nos Downlight Serie |
| 1004065 | LED driver , 30W 700mA  |
| 1004070 | LED driver , 40W 700mA  |
| 1004794 | NUMINOS® L , diffuser<br>Ellipse  |
| 1004795 | NUMINOS® L , diffuser<br>Prisma   |
| 1004796 | NUMINOS® L , diffuser<br>Frosted  |
| 1004797 | NUMINOS® L , diffuser<br>Wabe   |