




LID II UP/DOWN

wall-mounted light, 2700/3000K, 28W, PHASE, 100°, anthracite

Adjustable light colour via CCT switch (2700K/3000K), a high colour rendering index of over 80 and a long lifespan of 50,000 hours: the new LID II UP/DOWN wall light emits a powerful light with its upward and downward-facing, pivoting lamp heads which can be adjusted as needed. Simply perfect for atmospheric lighting of pathways, terraces or walls of homes and office buildings.



TECHNICAL DATA

Item no.	1007281
Number of different light outlets	2
IP Code	IP 65
Impact resistance class	IK 03
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	28 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	30
Number of luminaires at LS C16A	30
Level of inrush current	12 A
Duration of inrush current	40 µs
Temperature at glass (light emission)	70 °C
Stroboscopic effect (SVM)	0.08
Lumen	1500/1500 lm

Light Source

1807466	
---------	---

Colour temperature	2700/3000 Kelvin
Beam angle	100 °
Color	anthracite
CRI	80
LXXBXX data	L70B20
Service life	48000 h
Risk Group	1
Depth	6.5 cm
Diameter	22 cm
Net weight	0.94 kg
Gross weight	1.006 kg
BIG WHITE Page	711