




MEDO® PRO 30

wall- and ceiling-mounted light, round, 3000/4000K, 10W, DALI, Touch, 110°, white

Our design classic MEDO® has a new high-output addition: the MEDO® PRO. It impresses with its service life of L80B10@50,000h, eligible energy efficiency from 120 lm/W and a higher indirect light component. Efficiency is also the order of the day when it comes to installation, which is particularly fast thanks to our EasyBase. The improved protection code IP50 and an outstanding CRI>90 colour reproduction index ensure exceptional quality. Two elegant casing colours and a CCT switch that enables you to choose between 3000 K and 4000 K lets you personalise your lighting situation. The MEDO® PRO is available as a DALI and phase version, additionally you have the choice between opal (UGR<25) and prismatic (UGR<19) glass. As your most demanding projects deserve only the best lighting.



TECHNICAL DATA

Item no.	1007287
Number of different light outlets	2
IP Code	IP 50
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling,Ceiling with Acc.,Wall
Dimmable	Yes
Dimming technology	DALI,Touch
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	10 W
Ambient temperature	25 °C
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Operating efficiency (LOR)	0,9
Network rated standby power	0.26 W
Number of luminaires at LS B16A	72
Number of luminaires at LS C16A	122
Level of inrush current	52 A
Duration of inrush current	1 µs

Light Source

1807451	
---------	---

Accessories

1001952	MEDO 5m suspension , black
1001950	MEDO 5m suspension , white
135250	SUSPENSION SET , for MEDO round pendant, round, black, 5-wire
1001951	MEDO 5m suspension , silver-grey
135251	SUSPENSION SET , for MEDO round pendant, round, white, 5-wire
135254	SUSPENSION SET , for MEDO round pendant, round, silver-grey, 5-wire

Stroboscopic effect (SVM)	0.4
Lumen	1350/1350 lm
Colour temperature	3000/4000 Kelvin
Beam angle	110 °
Color	white
CRI	90
UGR ≤	25
LXXBXX data	L80B10
Service life	50000 h
Risk Group	1
Height	9.2 cm
Diameter	28 cm
Net weight	1.5 kg
Gross weight	1.605 kg
BIG WHITE Page	152