


## NEW TRIA® 68

recessed ceiling light, 2700K, 60°, IP 20, square, white

Discover the new generation of our NEW TRIA® recessed ceiling light with even more modularity for an individual lighting experience. Top sellers such as the NEW TRIA® 68 are also available as a complete set. The integrated LED MODULE, which is available with different light colours (2700K/3000K) and beam angles (38°/60°), provides lighting design options. The pivot range allows flexible alignment of the light. In black or white, the high-quality housing blends harmoniously into any room ambience. And thanks to the 68mm mounting ring supplied, the downlights can also be installed quickly and simply.



## TECHNICAL DATA

Item no.	1007395
Rotating or tilting	Tilttable
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	200 mA
Safety class	II
Wattage	8.3 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	88
Number of luminaires at LS C16A	149
Level of inrush current	3 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.4
Lumen	705 lm
Colour temperature	2700 Kelvin
Beam angle	60 °
Color	white

## Light Source

869193	
--------	---

CRI	90
LXXBXX data	L80B10
Service life	50000 h
Risk Group	1
Length	8.2 cm
Width	8.2 cm
Height	4 cm
Net weight	0.18 kg
Gross weight	0.193 kg
Shape of cut-out	round
Installation depth	4 cm
Installation diameter	6.8 cm
BIG WHITE Page	134