




NEW TRIA® 68

recessed ceiling light, 1800-3000K, 38°, IP 20, square, black

Discover the new generation of our NEW TRIA® recessed ceiling light with even more modularity for an individual lighting experience. Top sellers such as the NEW TRIA® 68 are available as a complete set. The integrated LED MODULE, which is available with dim-to-warm technology (1800-3000K) and different beam angles (38°/60°), provides lighting design options. The pivot range allows flexible alignment of the light, in black or white, the high-quality housing blends harmoniously into any room ambience. And thanks to the 68mm mounting ring supplied, the downlights can also be installed quickly and simply.



TECHNICAL DATA

Item no.	1007428
Rotating or tilting	Tilttable
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Dim-to-Warm, Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	250 mA
Safety class	II
Wattage	11 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	85
Number of luminaires at LS C16A	144
Level of inrush current	2 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.01
Lumen	70-700 lm
Colour temperature	1800-3000 Kelvin
Beam angle	38 °
Color	black

Light Source

879017	
--------	---

CRI	90
LXXBXX data	L80B10
Service life	50000 h
Risk Group	1
Length	8.2 cm
Width	8.2 cm
Height	4 cm
Net weight	0.21 kg
Gross weight	0.225 kg
Shape of cut-out	round
Installation depth	4.5 cm
Installation diameter	6.8 cm
BIG WHITE Page	135