




## NEW TRIA® UNIVERSAL 68

recessed ceiling light, 2500/3000/4000K, 38°, IP 20 / IP 65, round, black

Discover the new generation of our NEW TRIA® recessed ceiling light with even more modularity for an individual lighting experience. Top sellers such as the NEW TRIA® UNIVERSAL 68 are available as a complete set. Lighting design options are provided by the integrated multi-wattage LED MODULE, which is variable in terms of output and light intensity and available with different beam angles (38°/60°). While the CCT switch allows easy selection between 2500K, 3000K and 4000K, the pivot range ensures flexible alignment of the light. In black or white, the high-quality housing blends harmoniously into any room ambience. And thanks to the 68mm mounting ring supplied, the downlights can also be installed quickly and simply.



## TECHNICAL DATA

Item no.	1007442
IP Code	IP 20 / IP 65
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	100-180 mA
Safety class	II
Wattage	8.6 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	128
Number of luminaires at LS C16A	212
Level of inrush current	10 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0.02
Lumen	370/410/410 lm
Colour temperature	2500/3000/4000 Kelvin
Beam angle	38 °
Color	black
CRI	90

## Light Source

1807470	
---------	---

<b>LXXBXX data</b>	L80B10
<b>Service life</b>	50000 h
<b>Risk Group</b>	1
<b>Height</b>	5.25 cm
<b>Diameter</b>	8.2 cm
<b>Net weight</b>	0.24 kg
<b>Gross weight</b>	0.257 kg
<b>Shape of cut-out</b>	round
<b>Installation depth</b>	5.5 cm
<b>Installation diameter</b>	6.8 cm
<b>BIG WHITE Page</b>	137