



ONE CUBE UP/DOWN



pendant light, 300cm, 3000K, DALI 2, Touch, white

Clear the ring for new, round designs: the ONE CUBE pendant light adds another new member to the popular SLV light family that guarantees outstanding performance. The premium UP/DOWN version emits a DALI-dimmable, neutral-white (3000K) and upwards/downwards colour-neutral (CRI>90) light that is especially long-lasting at 50,000 hours. Perfect for upmarket living rooms or commercial areas. A well-rounded lighting experience.

TECHNICAL DATA

| | |
|-----------------------------------|-------------------|
| Item no. | 1007666 |
| Number of different light outlets | 2 |
| IP Code | IP 20 |
| Impact resistance | 0.35 Joule |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | DALI 2,Touch |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 2100 mA |
| Safety class | I |
| Wattage | 80 W |
| Minimum ambient temperature | -25 °C |
| Maximum ambient temperature | 35 °C |
| Network rated standby power | 0.5 W |
| Number of luminaires at LS B16A | 16 |
| Number of luminaires at LS C16A | 26 |
| Level of inrush current | 50 A |
| Duration of inrush current | 209 µs |
| Stroboscopic effect (SVM) | 0.4 |
| Lumen | 6000 lm |
| Colour temperature | 3000 Kelvin |

Light Source

| | |
|---------|---|
| 1807454 |  |
| 1807456 |  |

Accessories

| | |
|---------|--|
| 1007891 | |
| 1007746 | Felt plate acoustic , for ONE 80/ONE CUBE grey |

| | |
|----------------|----------|
| Beam angle | 44 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 19 |
| LXXBXX data | L80B10 |
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 4.2 cm |
| Diameter | 80.5 cm |
| Pendant length | 300 cm |
| Net weight | 3.8 kg |
| Gross weight | 4.066 kg |
| BIG WHITE Page | 189 |