


LID I

wall-mounted light, 2700/3000K, 15W, PHASE, 100°, anthracite

Adjustable light colour via CCT switch (2700K/3000K), a colour rendering index of over 80 and a long LED lifespan of 50,000 hours: the new LID I wall light emits a powerful light with its pivoting lamp head which can be adjusted as needed. Simply perfect for atmospheric lighting of pathways, terraces or walls of homes and office buildings.



TECHNICAL DATA

Item no.	1007667
IP Code	IP65
Impact resistance class	IK 07
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	15 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	61
Number of luminaires at LS C16A	61
Level of inrush current	6.5 A
Duration of inrush current	40 µs
Temperature at glass (light emission)	67 °C
Stroboscopic effect (SVM)	0.05
Lumen	900/1050 lm
Colour temperature	2700/3000 Kelvin

Light Source

1807471	
---------	---

Beam angle	100 °
Color	anthracite
CRI	80
LXXBXX data	L70B20
Service life	50000 h
Risk Group	0
Width	13 cm
Height	13 cm
Depth	9 cm
Net weight	1.23 kg
Gross weight	1.316 kg
BIG WHITE Page	713