




## DASAR® M

recessed floor light, round cover, 24°, 3000K, incl. DALI driver, stainless steel

Experience the highest quality of light with unique ease of installation. In addition, the DALI-controllable DASAR® recessed floor lights with a lifespan of 50,000 hours (L80-B50) set standards in terms of efficiency. The interchangeable reflectors with different beam angles of 15°, 30° and 50° offer a great deal of design freedom to effectively set the scene for facades. The reflectors can also be pivoted by 30°. And thanks to the separately available recessed fixing kit, the installation can be optimally adapted to your project planning.



## TECHNICAL DATA

Item no.	1007810
IP Code	IP67
Impact resistance class	IK 10
Assembly	Recessed
Assembly details	Ground with Acc.
Dimmable	Yes
Dimming technology	DALI, Touch
Number of through-wires	20
Mechanical loading	2 t
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	300 mA
Safety class	I
Wattage	6.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	63
Number of luminaires at LS C16A	100
Level of inrush current	8 A
Duration of inrush current	5.6 µs
Temperature at glass (light emission)	60 °C
Stroboscopic effect (SVM)	0
Lumen	450 lm

## Light Source

1642674	
---------	---

## Accessories

1007684	Reflector for DASAR® S/M , 36°
1007683	Reflector for DASAR® S/M , 15°
1007685	Reflector for DASAR® S/M , 50°
1007822	Mounting housing , for DASAR® M

Colour temperature	3000 Kelvin
Beam angle	24 °
Color	stainless steel
CRI	80
LXXBXX data	L80B50
Service life	50000 h
Depth	14 cm
Diameter	13 cm
Net weight	1.1 kg
Gross weight	1.177 kg
Shape of cut-out	round
Installation depth	18 cm
Installation diameter	31 cm