




ONE FLAT PD

pendant light, pendant length 180cm, 2700/3000K, PHASE, black

The new ONE FLAT pendant light adds another new member to the popular SLV light family that guarantees a truly elegant look. The flat ring emits a phase-dimmable, adjustable colour temperature (2700/3000K) and colour-neutral (CRI>90) light via CCT switch that is especially long-lasting at 50,000 hours. Perfect for upmarket living rooms or commercial areas. A well-rounded lighting experience.



TECHNICAL DATA

| | |
|---------------------------------|-----------------------------|
| Item no. | 1007855 |
| IP Code | IP20 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | Leading edge, trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 600 mA |
| Safety class | I |
| Wattage | 23 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 45 °C |
| Number of luminaires at LS B16A | 94 |
| Number of luminaires at LS C16A | 94 |
| Level of inrush current | 5 A |
| Duration of inrush current | 100 µs |
| Stroboscopic effect (SVM) | 0.4 |
| Lumen | 1300/1350 lm |
| Colour temperature | 2700/3000 Kelvin |
| Color | matt black |
| CRI | 90 |
| LXXBXX data | L80B10 |

Light Source

| | |
|---------|---|
| 2014567 |  |
|---------|---|

| | |
|-----------------------|----------|
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 2 cm |
| Diameter | 60 cm |
| Pendant length | 180 cm |
| Net weight | 3.276 kg |
| Gross weight | 5.274 kg |