



NEW TRIA® 155

DOUBLE LED module, 2700K, 38°, PHASE, black

Discover the new generation of our NEW TRIA® recessed ceiling lights with even more possibilities for an individual lighting experience. The DOUBLE LED module makes the design options even more diverse: the set includes two premium LED light sources with CRI>90 and 6 watts of power each, whose warm white light can not only be swivelled through 38°, but can also be phase dimmed using the driver supplied. You also have the choice between 2700 K and 3000 K. Combine the DOUBLE LED module with a NEW TRIA® 155 recessed ceiling ring of your choice.

TECHNICAL DATA

Item no.	1008005
Number of different light outlets	2
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	II
Wattage	13.6 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	85
Number of luminaires at LS C16A	144
Level of inrush current	2 A
Duration of inrush current	80 µs
Stroboscopic effect (SVM)	0.4
Lumen	1220 lm
Colour temperature	2700 Kelvin
Beam angle	38 °
Color	matt black

Light Source

	
--	---

Accessories

1008009	NEW TRIA® 155 , ceiling installation ring, L: 17 W: 9 H: 4 cm, two-lamp, IP 20, aluminium
1008008	NEW TRIA® 155 , ceiling installation ring, L: 17 W: 9 H: 4 cm, two-lamp, IP 20, white
1008007	NEW TRIA® 155 , ceiling installation ring, L: 17 W: 9 H: 4 cm, two-lamp, IP 20, black

CRI	90
LXXBXX data	L80B10
Service life	50000 h
Risk Group	1
Height	4 cm
Diameter	5 cm
Net weight	0.232 kg
Gross weight	0.265 kg