


QUIMERA

pendant light, pendant length 150cm, 2700/3000K, PHASE, brushed brass

The pendant, wall and table lamps in the QUIMERA range are characterised by timeless elegance. Each member is provided with a high-quality PVD coating, resulting in outstanding surface properties. The three colours Aged bronze, Matt nickel plated and Brushed brass are also shown to their best advantage. In addition, the elegant engraved lines in the glass ensure that the light appears indirect, which only enhances the elegant and timeless look.



TECHNICAL DATA

Item no.	1008033
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	8.2 W
Minimum ambient temperature	0 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	224
Number of luminaires at LS C16A	266
Level of inrush current	5 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0.02
Lumen	310/320 lm
Colour temperature	2700/3000 Kelvin

Light Source

2014569	
---------	---

Beam angle	360 °
Color	brushed brass
CRI	90
LXXBXX data	L80B50
Service life	50000 h
Risk Group	0
Height	47 cm
Diameter	7.6 cm
Pendant length	150 cm
Net weight	1.45 kg
Gross weight	1.98 kg