




## UNIVERSAL DOWN-LIGHT PHASE recessed light

IP20, 7W, 2700/3000/4000/6500K, 38°, without cover

Many qualities in one - this is how the SLV UNIVERSAL DOWNLIGHT is designed. The colour temperature can be quickly adjusted in four stages via CCT switch. The choice of 5 W or 7 W output is just as simple. And thanks to the lockable springs and Quick Connector Box, the downlight is quick and easy to install. In addition, the separately available covers in round or square and various colours allow the UNIVERSAL DOWNLIGHT to be used as a fixed downlight with IP65 or as a swivelling downlight with IP20.



### TECHNICAL DATA

Item no.	1008065
Rotating or tilting	tiltable
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	10
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	60/mA
Safety class	II
Wattage	7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	80
Number of luminaires at LS C16A	200
Level of inrush current	3 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.01
Lumen	670/680/690/680 lm

## Light Source

	
--	---

### Accessories

1007191	UNIVERSAL DOWN-LIGHT cover , for down-light IP20, pivoting, round, gold matt
1008069	UNIVERSAL DOWN-LIGHT cover , for Down-light, IP65, round, aluminium
1008096	UNIVERSAL DOWN-LIGHT cover , for down-light, IP65, square, black
1008068	UNIVERSAL DOWN-LIGHT cover , for Down-light, IP65, round, white
1008098	UNIVERSAL DOWN-LIGHT cover , for down-light, IP65, square, gold matt
1008067	UNIVERSAL DOWN-LIGHT cover , for Down-light IP65, round, black
1007186	UNIVERSAL DOWN-LIGHT cover , for down-light IP20, pivoting, square, aluminium
1007091	UNIVERSAL DOWN-LIGHT Cover , for Down-light IP20, pivoting, round, black
1008070	UNIVERSAL DOWN-LIGHT cover , for down-light, IP65, round, gold matt
1008097	UNIVERSAL DOWN-LIGHT cover , for down-light, IP65, square, aluminium
1007093	UNIVERSAL DOWN-LIGHT Cover , for Down-light IP20, pivoting, round, aluminium
1007194	UNIVERSAL DOWN-LIGHT cover , for down-light IP20, pivoting, square, gold matt
1007185	UNIVERSAL DOWN-LIGHT cover , for down-light IP20, pivoting, square, white
1007092	UNIVERSAL DOWN-LIGHT Cover , for Down-light IP20, pivoting, round, white

Colour temperature	2700/3000/4000/6500 Kelvin
Beam angle	38 °
Color	matt black
CRI	90
LXXBXX data	L80B50
Service life	50000 h
Risk Group	1
Height	5.7 cm
Diameter	8.5 cm
Net weight	0.264 kg
Gross weight	0.312 kg
Shape of cut-out	round
Installation depth	7 cm
Installation diameter	6.8 cm

1008095	UNIVERSAL DOWN-LIGHT cover , for down-light, IP65, square, white
1007184	UNIVERSAL DOWN-LIGHT cover , for down-light IP20, pivoting, square, black