




ONE LINEAR 70

wall-mounted light, UP/DOWN, 2700/3000K, PHASE, black

ONE LINEAR extends the popular SLV luminaire family with high-quality wall luminaires that are available in two new lengths (50 cm and 70 cm). The up/down lighting with an adjustable colour temperature (2700K/3000K) and the PHASE dimming function conjures up an extremely elegant and flexible lighting mood. Thanks to its IP44 protection rating, the ONE LINEAR wall light is a stylish highlight not only in hotels, restaurants and living rooms, but also in bathrooms.



TECHNICAL DATA

| | |
|-----------------------------------|-----------------------------|
| Item no. | 1008081 |
| Number of different light outlets | 2 |
| IP Code | IP44 |
| Assembly | Surface |
| Assembly details | Wall |
| Dimmable | Yes |
| Dimming technology | Leading edge, trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 500 mA |
| Safety class | I |
| Wattage | 20 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 45 °C |
| Number of luminaires at LS B16A | 114 |
| Number of luminaires at LS C16A | 114 |
| Level of inrush current | 5 A |
| Duration of inrush current | 100 µs |
| Stroboscopic effect (SVM) | 0.4 |
| Lumen | 990/1100 lm |
| Colour temperature | 2700/3000 Kelvin |
| Beam angle | 120 ° |
| Color | matt white/matt black |

Light Source

| | | | |
|---------|---|--------------|---------|
| 1679802 |  | CRI | 90 |
| | | LXXBXX data | L80B10 |
| | | Service life | 50000 h |
| | | Risk Group | 1 |
| | | Width | 70.5 cm |
| | | Height | 4.2 cm |
| | | Depth | 8.1 cm |
| | | Net weight | 0.92 kg |
| | | Gross weight | 1 kg |