


ONE LINEAR 50

wall-mounted light, UP/DOWN, 2700/3000K, PHASE, black

ONE LINEAR extends the popular SLV luminaire family with high-quality wall luminaires that are available in two new lengths (50 cm and 70 cm). The up/down lighting with an adjustable colour temperature (2700K/3000K) and the PHASE dimming function conjures up an extremely elegant and flexible lighting mood. Thanks to its IP44 protection rating, the ONE LINEAR wall light is a stylish highlight not only in hotels, restaurants and living rooms, but also in bathrooms.



TECHNICAL DATA

| | |
|-----------------------------------|-----------------------|
| Item no. | 1008084 |
| Number of different light outlets | 2 |
| IP Code | IP44 |
| Assembly | Surface |
| Assembly details | Wall |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 350 mA |
| Safety class | I |
| Wattage | 14 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 45 °C |
| Number of luminaires at LS B16A | 160 |
| Number of luminaires at LS C16A | 160 |
| Level of inrush current | 5 A |
| Duration of inrush current | 100 µs |
| Stroboscopic effect (SVM) | 0.4 |
| Lumen | 730/810 lm |
| Colour temperature | 2700/3000 Kelvin |
| Beam angle | 120 ° |
| Color | matt white/matt black |

Light Source

| | |
|---------|---|
| 1679804 |  |
|---------|---|

| | |
|---------------------|---------|
| CRI | 90 |
| LXXBXX data | L80B10 |
| Service life | 50000 h |
| Risk Group | 1 |
| Width | 52.5 cm |
| Height | 4.2 cm |
| Depth | 8.1 cm |
| Net weight | 0.77 kg |
| Gross weight | 0.85 kg |