




## **ABRIDOR POLE 60**

## floor lamp, HYBRID, 2200/2700K, IP65 anthracite

The ABRIDOR Outdoor Hybrid lighting family offers a versatile and energy-efficient solution with automatic switching between solar and mains power: in sunny regions, the light can be operated all year round using only solar energy, while in less sunny areas it can also be connected to 230V mains power. This means that the light with the solar panel also works completely without a power connection, with the batteries being charged via the panel. It is certified to IP65, resistant to sea air and equipped with a T-connector. Three modes ensure optimum and energy-efficient operation.



## **TECHNICAL DATA**

Item no.	1008543
IP Code	IP65
Impact resistance class	IK 07
Impact resistance	2 Joule
Assembly	Surface
Assembly details	Ground
Number of through-wires	80
Primary nominal voltage	100-240V ~50/60Hz
Secondary power / voltage	380 mA
Safety class	I
Wattage	6.8 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	45 °C
Rated standby power	0.5 W
Number of luminaires at LS B16A	200
Number of luminaires at LS C16A	200
Level of inrush current	6.9 A
Duration of inrush current	68 µs
Stroboscopic effect (SVM)	0.001
Lumen	600/650 lm
Colour temperature	2200/2700 Kelvin
Color	matt anthracite



CRI	80
LXXBXX data	L80B50
Service life	30000 h
Length	19.6 cm
Width	18.4 cm
Height	60 cm
Net weight	1.85 kg
Gross weight	3.08 kg