




## ONE

wall and ceiling-mounted light, round, 2700/3000K, 14-W, PHASE, 130°, black

Reduced and modern at the same time, the lights of the ONE family attract all eyes. This also applies to the new ONE surface-mounted wall and ceiling luminaires, which extend the popular SLV family with their upward and downward light distribution. They are available in three trendy colours, in two sizes each, with adjustable light colour (2700K/3000K) via CCT switch and phase cut-off or DALI controllable.



## TECHNICAL DATA

Item no.	1008547
Number of different light outlets	2
IP Code	IP20
Assembly	Surface
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	14 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	160
Number of luminaires at LS C16A	160
Level of inrush current	5 A
Duration of inrush current	100 µs
Lumen	450/450 lm
Colour temperature	2700/3000 Kelvin
Color	black
CRI	90
Service life	50000 h
Height	11.5 cm

<b>Diameter</b>	40 cm
<b>Net weight</b>	1.4 kg
<b>Gross weight</b>	3.22 kg