




KADUX

recessed ceiling light, single, 4000K, DALI 2, touch, 30°, white

Experience high light output and efficiency for use in shops and retail environments: KADUX is our gimbal-mounted recessed ceiling luminaire, available as a single or double-lamp version in white or black and various colour temperatures (3000K/4000K). Thanks to the quick-connection box in a closed steel housing, the light is easy to install and is both robust and durable.



TECHNICAL DATA

Item no.	1008569
Number of different light outlets	1
IP Code	IP20
Assembly	Recessed
Dimmable	Yes
Dimming technology	DALI,Touch
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	700
Safety class	II
Wattage	27 W
Ambient temperature	85 °C
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	74
Number of luminaires at LS C16A	100
Level of inrush current	15 A
Duration of inrush current	100 µs
Lumen	3350 lm
Colour temperature	4000 Kelvin
Color	white/black
CRI	90
Binning	6 SDCM

Service life	50000 h
Risk Group	1
Length	19.5 cm
Width	19.5 cm
Height	12.5 cm
Net weight	1.48 kg
Gross weight	1.92 kg
Shape of cut-out	square
Installation length	17 cm
Installation width	17 cm
Installation depth	12.5 cm