




## KADUX

recessed ceiling light, double, 3000K, DALI 2, touch, 30°, black

Experience high light output and efficiency for use in shops and retail environments: KADUX is our gimbal-mounted recessed ceiling luminaire, available as a single or double-lamp version in white or black and various colour temperatures (3000K/4000K). Thanks to the quick-connection box in a closed steel housing, the light is easy to install and is both robust and durable.



## TECHNICAL DATA

Item no.	1008572
Number of different light outlets	2
IP Code	IP20
Assembly	Recessed
Dimmable	Yes
Dimming technology	DALI,Touch
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	1400
Safety class	II
Wattage	54 W
Ambient temperature	80 °C
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	37
Number of luminaires at LS C16A	74
Level of inrush current	65 A
Duration of inrush current	100 µs
Lumen	3150 lm
Colour temperature	3000 Kelvin
Color	black/black
CRI	90
Binning	6 SDCM

<b>Service life</b>	50000 h
<b>Risk Group</b>	1
<b>Length</b>	37 cm
<b>Width</b>	19.5 cm
<b>Height</b>	12.5 cm
<b>Net weight</b>	2.8 kg
<b>Gross weight</b>	3.24 kg
<b>Shape of cut-out</b>	square
<b>Installation length</b>	34.5 cm
<b>Installation width</b>	17 cm
<b>Installation depth</b>	12.5 cm