




## DOWNLIGHT C

200 8/16/24W 940 IP54

Discover our technical product range: SLVtec. With state-of-the-art LED technology, we offer energy-efficient and functional lighting solutions for indoor and outdoor use. From wet room lights to high-bay spotlights – our high-quality products impress with functionality and a fair price-performance ratio. These include the DOWNLIGHT C recessed luminaires, which are ideal for general lighting in commercial environments. They are available in two different cut-outs (150 mm and 200 mm) and offer a colour temperature of 3000K or 4000K. You can also choose from an on/off version with switchable system output and a DALI-controllable version. With their eligible energy efficiency and a lumen output of up to 3,100 lm, you can experience sustainable lighting in commercial spaces.



## TECHNICAL DATA

Item no.	1008624
IP Code	IP54
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Number of through-wires	33
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	200/400/600 mA
Safety class	II
Wattage	8 W
Ambient temperature	70 °C
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	33
Number of luminaires at LS C16A	57
Level of inrush current	16 A
Duration of inrush current	100 µs
Lumen	1080/2050/3100 lm
Colour temperature	4000 Kelvin
Color	white
CRI	90
UGR ≤	22

<b>Service life</b>	70000 h
<b>Height</b>	9.6 cm
<b>Diameter</b>	22.6 cm
<b>Net weight</b>	0.7 kg
<b>Gross weight</b>	0.8 kg
<b>Shape of cut-out</b>	round
<b>Installation depth</b>	10 cm
<b>Installation diameter</b>	20.5 cm