




## DOWNLIGHT C

DALI 150 20W 930 IP54

Discover our technical product range: SLVtec. With state-of-the-art LED technology, we offer energy-efficient and functional lighting solutions for indoor and outdoor use. From wet room lights to high-bay spotlights – our high-quality products impress with functionality and a fair price-performance ratio. These include the DOWNLIGHT C recessed luminaires, which are ideal for general lighting in commercial environments. They are available in two different cut-outs (150 mm and 200 mm) and offer a colour temperature of 3000K or 4000K. You can also choose from an on/off version with switchable system output and a DALI-controllable version. With their eligible energy efficiency and a lumen output of up to 3,100 lm, you can experience sustainable lighting in commercial spaces.



## TECHNICAL DATA

Item no.	1008625
IP Code	IP54
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Dimmable	Yes
Dimming technology	DALI
Number of through-wires	18
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	500 mA
Safety class	II
Wattage	20 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	18
Number of luminaires at LS C16A	39
Level of inrush current	15 A
Duration of inrush current	300 µs
Lumen	2250 lm
Colour temperature	3000 Kelvin
Color	white
CRI	90

<b>UGR <math>\leq</math></b>	22
<b>Service life</b>	70000 h
<b>Height</b>	8.6 cm
<b>Diameter</b>	17.6 cm
<b>Net weight</b>	0.5 kg
<b>Gross weight</b>	0.6 kg
<b>Shape of cut-out</b>	round
<b>Installation depth</b>	9 cm
<b>Installation diameter</b>	15.5 cm