




DOWNLIGHT C

DALI 200 24W 930 IP54

Discover our technical product range: SLVtec. With state-of-the-art LED technology, we offer energy-efficient and functional lighting solutions for indoor and outdoor use. From wet room lights to high-bay spotlights – our high-quality products impress with functionality and a fair price-performance ratio. These include the DOWNLIGHT C recessed luminaires, which are ideal for general lighting in commercial environments. They are available in two different cut-outs (150 mm and 200 mm) and offer a colour temperature of 3000K or 4000K. You can also choose from an on/off version with switchable system output and a DALI-controllable version. With their eligible energy efficiency and a lumen output of up to 3,100 lm, you can experience sustainable lighting in commercial spaces.



TECHNICAL DATA

Item no.	1008627
IP Code	IP54
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Dimmable	Yes
Dimming technology	DALI
Number of through-wires	18
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	600 mA
Safety class	II
Wattage	24 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	18
Number of luminaires at LS C16A	39
Level of inrush current	15 A
Duration of inrush current	300 µs
Lumen	2850 lm
Colour temperature	3000 Kelvin
Color	white
CRI	90

UGR ≤	22
Service life	70000 h
Height	9.6 cm
Diameter	22.6 cm
Net weight	0.7 kg
Gross weight	0.8 kg
Shape of cut-out	round
Installation depth	10 cm
Installation diameter	20.5 cm