




## MEDO® 30

recessed ceiling light, frameless, 3000/4000K, 70°, IP20, round, white

The best MEDO® of all time is also available as a recessed ceiling light in four different sizes, including frame or frameless. It impresses with a longer service life and subsidised energy efficiency of over 140 lm/W. The colour rendering index CRI>90 ensures true-colour and, with UGR<19, virtually glare-free light quality, making it suitable for use in offices. The CCT switch enables you to choose between 3000 K and 4000 K, letting you personalise your lighting situation. Please note that the driver and strain relief must be purchased separately.



## TECHNICAL DATA

Item no.	1008630
IP Code	IP20
Assembly	Recessed
Secondary power / voltage	250 mA
Safety class	III
Wattage	8 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Lumen	1150/1200 lm
Colour temperature	3000/4000 Kelvin
Color	white
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	9.5 cm
Diameter	28 cm
Net weight	0.9 kg
Gross weight	2.36 kg
Shape of cut-out	round
Installation depth	13 cm
Installation diameter	29 cm

## Accessories

1006871	NUMINOS® PROJEC-TOR XS , recessed ceiling light, 2700 K, 40°, cylindrical, black / white
1006870	NUMINOS® PROJEC-TOR XS , recessed ceiling light, 2700 K, 40°, cylindrical, black / black
1008673	Strain relief through-wirable , for DALI dimmable drivers: 1008666, 1008667, 1008668
1008672	Strain relief , standard, for DALI-dimmable drivers: 1008666, 1008667, 1008668
1008699	
1008660	LED driver 10W 180-270mA , PHASE
1008666	LED driver 15W , 100-700mA, DALI