




NOBLO®

wall and ceiling-mounted light, triple, round,
2000-3000K, 22W, dim-to-warm, PHASE, 36°, white

Discover the technical upgrade of the NOBLO® spotlights, which impress with their slimline design. The rotating and swivelling spotlights are ideal for both wall and ceiling mounting. With two timeless housing colours and one, two or three light outlets, they can be used flexibly. The NO-BLO® spotlights are available with 2700K, 3000K or as a dim-to-warm version for customised lighting design. Additional visual accents can be created with the separately available decorative rings.



TECHNICAL DATA

Item no.	1008705
Number of different light outlets	3
IP Code	IP20
Assembly	Surface
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	350
Safety class	I
Wattage	22 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	107
Number of luminaires at LS C16A	107
Level of inrush current	5 A
Duration of inrush current	100 µs
Lumen	10-1360 lm
Colour temperature	2000-3000 Kelvin
Color	white
CRI	90
Service life	40000 h
Risk Group	1

Length	40 cm
Width	10.5 cm
Height	12.7 cm
Net weight	0.86 kg
Gross weight	1.2 kg

Accessories

1008484	NOBLO® , decorative ring, gold
1008487	NOBLO® , decorative ring, bronze
1008486	NOBLO® , decorative ring, copper
1008483	NOBLO® , decorative ring, white
1008482	NOBLO® , decorative ring, black
1008485	NOBLO® , decorative ring, grey