


SIGHT EASY

3~ spot, rectangular, 4000K, 41W, DALI, 25°, white

SIGHT EASY extends the luminaire family with linear lighting for 3-phase track systems. It is specially designed for commercial environments such as grocery shops: With its double asymmetrical 25° optics, it can illuminate two shelves on both sides with just one product, guaranteeing efficient illumination. The integrated multipower or DALI driver enables flexible customisation on site. The luminaire also impresses with its high energy efficiency of almost 160 lm/W. The SIGHT EASY luminaire is available in black and white and with colour temperatures of 3000K and 4000K.



TECHNICAL DATA

| | |
|---------------------------------------|-------------------------|
| Item no. | 1008731 |
| IP Code | IP20 |
| Impact resistance class | IK 06 |
| Impact resistance | 1 Joule |
| Assembly | Surface |
| Dimmable | Yes |
| Dimming technology | DALI |
| Primary nominal voltage | 220-240V ~50/60 Hz |
| Secondary power / voltage | 250/300/350/400 mA |
| Safety class | I |
| Wattage | 41 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Number of luminaires at LS B16A | 24 |
| Number of luminaires at LS C16A | 40 |
| Level of inrush current | 32 A |
| Duration of inrush current | 170 µs |
| Temperature at glass (light emission) | 33.5 °C |
| Lumen | 7100/8200/9600/10900 lm |
| Colour temperature | 4000 Kelvin |
| Color | black |
| CRI | 90 |

| | |
|------------------------------|---------|
| UGR \leq | 25 |
| Service life | 50000 h |
| Length | 150 cm |
| Width | 6.4 cm |
| Height | 2 cm |
| Net weight | 1.2 kg |
| Gross weight | 1.72 kg |