




TRACKSPOT C 3 Ph. 17W 930 36°

White

The TRACKSPOT C 3-phase spotlight, which is compatible with S-Track and Eutrac systems, is the ideal choice for demanding commercial projects with a moderate budget, where high efficiency and the lowest possible energy consumption are the key points of focus. With an energy efficiency of over 145 lm/W, excellent colour rendering thanks to CRI 90, and a high luminous flux of up to 4,400 lumens, the luminaire offers a lighting solution that is perfect for small and large commercial areas. Thanks to a service life of 50,000 hours (L80B50), the TRACKSPOT C also ensures long-term reliability and reduces maintenance costs. Available in different versions with 17W or 29W, beam angles of 36° or 50°, in 3,000 K and 4,000 K, the TRACKSPOT C comes in black and white versions. This flexibility enables harmonious integration into different room concepts.



TECHNICAL DATA

| | |
|-----------------------------------|--------------------|
| Item no. | 1008860 |
| Number of different light outlets | 1 |
| IP Code | IP20 |
| Assembly details | Ceiling, Wall |
| Primary nominal voltage | 220-240V ~50/60 Hz |
| Secondary power / voltage | 450 mA |
| Safety class | II |
| Wattage | 17 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Number of luminaires at LS B16A | 21 |
| Number of luminaires at LS C16A | 34 |
| Level of inrush current | 45 A |
| Duration of inrush current | 400 µs |
| Lumen | 2450 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 36 ° |
| CRI | 90 |
| Service life | 50000 h |
| Length | 10.5 cm |
| Height | 14 cm |
| Diameter | 10 cm |

Light Source

| | |
|---------|---|
| 2190383 |  |
|---------|---|

| | |
|--------------|---------|
| Net weight | 0.72 kg |
| Gross weight | 0.88 kg |