

NUMINOS® MOVE XS

white / black recessed ceiling light, 2700K 20°

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Like with the NUMINOS® MOVE XS recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

TECHNICAL DATA

Item no.:	1005562
Secondary power / secondary voltage	200mA
Height	5.5 cm
Diameter	8.0 cm
Installation diameter	6.8 cm
Installation depth	11.0 cm
Net weight	0.11 kg
Gross weight	0.118 kg
IP Code	IP 20
Safety class	III
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Lumen	640 lm
Colour temperature	2700 Kelvin
Beam angle	20 °
Color	white
CRI	90
UGR ≤	16
LXXBXX data	L80B50
Minimum ambient temperature	-20 °C

Maximum ambient temperature

40 °C

Accessories

1005609	LED Driver , 200mA 10W PHASE, Quick Connector
1005610	LED Driver , 200mA 10W, Quick Connector
1005611	LED Driver , 200mA 13,5W DALI dimmable, Quick Connector
1005612	NUMINOS® XS , diffuser
1005613	NUMINOS® XS , transparent diffuser
1005614	NUMINOS® XS , frosted diffuser
1005615	NUMINOS® XS , black diffuser

Notes
