NUMINOS® MOVE XS

white / black recessed ceiling light, 3000K 40°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you provide a thousand lighting design possibilities. Also with the NUMINOS® MOVE XS recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. This means that simple installation is a mere formality. When will you choose SLV's modular variety?

TECHNICAL DATA

Item no.:	1005583
Secondary power / secondary volta- ge	200mA
Height	5.5 cm
Diameter	8.0 cm
Installation diameter	6.8 cm
Installation depth	11.0 cm
Net weight	0.11 kg
Gross weight	0.118 kg
IP Code	IP 20
Safety class	Ш
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Lumen	670 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	white
CRI	90
UGR≤	22
LXXBXX data	L80B50
Minimum ambient temperature	-20 °C

1005500





Maximum ambient temperature	40 °C

Accessories

1005609	LED Driver , 200mA 10W PHASE, Quick Connector
1005610	LED Driver , 200mA 10W, Quick Connector
1005611	LED Driver , 200mA 13,5W DALI dimma- ble, Quick Connector
1005612	NUMINOS® XS , diffuser
1005613	NUMINOS® XS , transparent diffuser
1005614	NUMINOS® XS , frosted diffuser
1005615	NUMINOS® XS , black diffuser

Notes			