

NUMINOS® MOVE XS

white / black recessed ceiling light, 3000K 55°

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. This also includes NUMINOS® MOVE XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When will you choose SLV's modular variety?

TECHNICAL DATA

| | |
|-------------------------------------|-------------|
| Item no.: | 1005586 |
| Secondary power / secondary voltage | 200mA |
| Height | 5.5 cm |
| Diameter | 8.0 cm |
| Installation diameter | 6.8 cm |
| Installation depth | 11.0 cm |
| Net weight | 0.11 kg |
| Gross weight | 0.118 kg |
| IP Code | IP 20 |
| Safety class | III |
| Impact resistance class | IK02 |
| Impact resistance | 0,2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Lumen | 690 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 55 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 25 |
| LXXBXX data | L80B50 |
| Minimum ambient temperature | -20 °C |

Maximum ambient temperature

40 °C

Accessories

| | |
|---------|---|
| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector |
| 1005610 | LED Driver , 200mA 10W, Quick Connector |
| 1005611 | LED Driver , 200mA 13,5W DALI dimmable, Quick Connector |
| 1005612 | NUMINOS® XS , diffuser |
| 1005613 | NUMINOS® XS , transparent diffuser |
| 1005614 | NUMINOS® XS , frosted diffuser |
| 1005615 | NUMINOS® XS , black diffuser |

Notes
