

NUMINOS® GIMBLE XS

white / black recessed ceiling light, 2700K 20°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® GIMBLE XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

TECHNICAL DATA

| | |
|-------------------------------------|-------------|
| Item no.: | 1005822 |
| Number of different light outlets | 1 |
| Secondary power / secondary voltage | 200mA |
| Height | 5.7 cm |
| Diameter | 8.0 cm |
| Installation diameter | 6.8 cm |
| Installation depth | 11.0 cm |
| Net weight | 0.11 kg |
| Gross weight | 0.118 kg |
| Safety class | III |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Lumen | 640 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 20 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 16 |

Accessories

| | |
|---------|---------------------------------------------------------|
| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector |
| 1005610 | LED Driver , 200mA 10W, Quick Connector |
| 1005611 | LED Driver , 200mA 13,5W DALI dimmable, Quick Connector |
| 1005612 | NUMINOS® XS , diffuser |
| 1005613 | NUMINOS® XS , transparent diffuser |
| 1005614 | NUMINOS® XS , frosted diffuser |
| 1005615 | NUMINOS® XS , black diffuser |

Notes
