

## **NUMINOS® GIMBLE XS**

## black recessed ceiling light, 4000K $40^{\circ}$

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® GIMBLE XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.

## **TECHNICAL DATA**

| Item no.:                                    | 1005852                          |
|--|----------------------------------|
| Number of different light outlets            | 1                                |
| Secondary power / secondary volta-<br>ge     | 200mA                            |
| Height                                       | 5.7 cm                           |
| Diameter                                     | 8.0 cm                           |
| Installation diameter                        | 6.8 cm                           |
| Installation depth                           | 11.0 cm                          |
| Net weight                                   | 0.11 kg                          |
| Gross weight                                 | 0.118 kg                         |
| Safety class                                 | Ш                                |
| Assembly                                     | Recessed                         |
|  |                                  |
| Assembly details                             | Ceiling                          |
| Assembly details  Lumen                      | Ceiling 700 lm                   |
|  |                                  |
| Lumen  | 700 lm                           |
| Lumen Colour temperature                     | 700 lm<br>4000 Kelvin            |
| Lumen  Colour temperature  Beam angle        | 700 lm<br>4000 Kelvin<br>40 °    |
| Lumen  Colour temperature  Beam angle  Color | 700 lm  4000 Kelvin  40 °  black |



## **Accessories**

| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector                |
|---------|--|
| 1005610 | LED Driver , 200mA 10W, Quick Connector                      |
| 1005611 | LED Driver , 200mA 13,5W DALI dimma-<br>ble, Quick Connector |
| 1005612 | NUMINOS® XS , diffuser                                       |
| 1005613 | NUMINOS® XS , transparent diffuser                           |
| 1005614 | NUMINOS® XS , frosted diffuser                               |
| 1005615 | NUMINOS® XS , black diffuser                                 |
|         |  |

| Notes |  |  |  |
|-------|--|--|--|
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |