NUMINOS® GIMBLES

black recessed ceiling light, 3000K $20^{\circ}\,$

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® GIMBLE S recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

TECHNICAL DATA

| Item no.: | 1005885 |
|--|-------------|
| Number of different light outlets | 1 |
| Secondary power / secondary volta- ge | 250mA |
| Height | 7.0 cm |
| Diameter | 10.0 cm |
| Installation diameter | 9.0 cm |
| Installation depth | 7.0 cm |
| Net weight | 0.18 kg |
| Gross weight | 0.193 kg |
| Safety class | III |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Lumen | 690 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 20 ° |
| Color | black |
| CRI | 90 |
| UGR≤ | 19 |
| | • |



Accessories

| 1004055 | LED driver , 6.5-10W 250mA PHASE |
|---------|----------------------------------|
| 1004058 | LED driver , 6.5-10W 250mA |
| 1004067 | LED driver , 15W 250mA DALI |
| 1004786 | NUMINOS® S , diffuser Ellipse |
| 1004787 | NUMINOS® S , diffuser Prisma |
| 1004788 | NUMINOS® S , diffuser Frosted |
| 1004789 | NUMINOS® S , diffuser Wabe |
| | |

| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |