

NUMINOS® GIMBLE M

black recessed ceiling light, 3000K 20°

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. The diverse downlights and spotlights make a thousand lighting design options possible. Also with the NUMINOS® GIMBLE M recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. This means that simple installation is a mere formality. When do you choose NUMINOS ® from SLV?

TECHNICAL DATA

| | |
|-------------------------------------|-------------|
| Item no.: | 1005939 |
| Number of different light outlets | 1 |
| Secondary power / secondary voltage | 500mA |
| Height | 9.5 cm |
| Diameter | 13.5 cm |
| Installation diameter | 12.0 cm |
| Installation depth | 9.5 cm |
| Net weight | 0.42 kg |
| Gross weight | 0.449 kg |
| Safety class | III |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Lumen | 1500 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 20 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 22 |

Accessories

| | |
|---------|---|
| 1004054 | LED driver , 30W 500mA PHASE |
| 1004064 | LED driver , 21-29.5W 500/600/700mA |
| 1004069 | LED driver , 1.5-40,6W 230/350/500/700mA |
| 1004790 | NUMINOS® M , diffuser Ellipse |
| 1004791 | NUMINOS® M , diffuser Prisma |
| 1004792 | NUMINOS® M , diffuser Frosted |
| 1004793 | NUMINOS® M , diffuser Wabe |

Notes
