

## **NUMINOS® GIMBLE L**

black / white recessed ceiling light, 3000K  $20^{\circ}\,$ 

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. This also includes NUMINOS® GIMBLE L, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

## **TECHNICAL DATA**

Item no.:	1006002
Number of different light outlets	1
Secondary power / secondary voltage	700mA
Height	11.5 cm
Diameter	16.0 cm
Installation diameter	14.5 cm
Installation depth	11.5 cm
Net weight	0.6 kg
Gross weight	0.642 kg
Safety class	III
Assembly	Recessed
Assembly details	Recessed  Ceiling
Assembly details	Ceiling
Assembly details  Lumen	Ceiling 2150 lm
Assembly details  Lumen  Colour temperature	Ceiling 2150 lm 3000 Kelvin
Assembly details  Lumen  Colour temperature  Beam angle	Ceiling 2150 lm 3000 Kelvin 20 °
Assembly details  Lumen  Colour temperature  Beam angle  Color	Ceiling 2150 lm 3000 Kelvin 20 ° white



## **Accessories**

1004062	LED driver , 21-29.5W 500/600/700mA
1004065	LED driver , 30W 700mA
1004070	LED driver , 40W 700mA
1004794	NUMINOS® L , diffuser Ellipse
1004795	NUMINOS® L , diffuser Prisma
1004796	NUMINOS® L , diffuser Frosted
1004797	NUMINOS® L , diffuser Wabe

Notes			