## NUMINOS® GIMBLE L

black recessed ceiling light, 4000K  $20^{\circ}\,$ 

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® GIMBLE L recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.

## **TECHNICAL DATA**

Item no.:	1006011
Number of different light outlets	1
Secondary power / secondary volta- ge	700mA
Height	11.5 cm
Diameter	16.0 cm
Installation diameter	14.5 cm
Installation depth	11.5 cm
Net weight	0.6 kg
Gross weight	0.642 kg
Safety class	III
Assembly	Recessed
Assembly details	Recessed  Ceiling
Assembly details	Ceiling
Assembly details  Lumen	Ceiling 2350 lm
Assembly details  Lumen  Colour temperature	Ceiling 2350 lm 4000 Kelvin
Assembly details  Lumen  Colour temperature  Beam angle	Ceiling 2350 lm 4000 Kelvin 20 °
Assembly details  Lumen  Colour temperature  Beam angle  Color	Ceiling 2350 lm 4000 Kelvin 20 ° black



## **Accessories**

1004062	LED driver , 21-29.5W 500/600/700mA
1004065	LED driver , 30W 700mA
1004070	LED driver , 40W 700mA
1004794	NUMINOS® L , diffuser Ellipse
1004795	NUMINOS® L , diffuser Prisma
1004796	NUMINOS® L , diffuser Frosted
1004797	NUMINOS® L , diffuser Wabe

Notes			