

NUMINOS® GIMBLE L

white / chrome recessed ceiling light, 4000K 40°

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® GIMBLE L recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

TECHNICAL DATA

| | |
|-------------------------------------|-------------|
| Item no.: | 1006025 |
| Number of different light outlets | 1 |
| Secondary power / secondary voltage | 700mA |
| Height | 11.5 cm |
| Diameter | 16.0 cm |
| Installation diameter | 14.5 cm |
| Installation depth | 11.5 cm |
| Net weight | 0.6 kg |
| Gross weight | 0.642 kg |
| Safety class | III |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Lumen | 2350 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 40 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 22 |

Accessories

| | |
|---------|-------------------------------------|
| 1004062 | LED driver , 21-29.5W 500/600/700mA |
| 1004065 | LED driver , 30W 700mA |
| 1004070 | LED driver , 40W 700mA |
| 1004794 | NUMINOS® L , diffuser Ellipse |
| 1004795 | NUMINOS® L , diffuser Prisma |
| 1004796 | NUMINOS® L , diffuser Frosted |
| 1004797 | NUMINOS® L , diffuser Wabe |

Notes
